

CEPSA 2T UNIVERSAL

Description



A lubricant oil for all types of moderately powered two-stroke engines under normal conditions of use. Recommended for gardening and DIY tools and for low-capacity motorcycles and mopeds.

Applications

- Suitable for use when the power/size ratio of the motor is crucial and, generally, for small motors that do not require emissions control.
- In gardening and DIY tools with moderate demands in terms of operation and performance: lawnmowers, chainsaws, electrical generators, irrigation pumps, etc.
- Compatible with all types of petrol, it should be used as a 2% premix or at the dose recommended by the manufacturer.

Product Performance

- Its viscosity and special additivation allow rapid greasing of all parts of the engine, providing a higher starting torque and better lubrication than other conventional oils.
- Provides optimal protection and engine cleaning, with no seizure, due to its high detergent power.
- Its good dispersant capacity prevents deposits from forming in the pistons and ports, thus extending the lifespan of the spark plugs without fouling.

Specifications

- JASO FB
- ISO L-EGB
- API TC

Typical Characteristics

CHARACTERISTIC	UNITS	METHOD	CEPSA 2T UNIVERSAL
Density at 15°C	g/ml	ASTM D4052	0.883
P/M Flash Point	°C	ASTM D93	94
Pour Point	°C	ASTM D5950	-21
Viscosity at 100°C	cSt	ASTM D445	8.79
Viscosity Index	-	ASTM D2270	116
Total Base Number (TBN)	mg KOH/g	ASTM D2896	1
Color	-	ASTM D1500	Red

Health & Safety and Environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.