

CEPSA AURIGA TE 55 10W30

Description



Multigrade universal oil for tractor transmission (UTTO) which incorporates the last technology. Meets the requirements of modern agricultural equipment and is suitable for use in wet brakes, hydraulic systems, clutches and torque converters.

Applications

- High oxidation stability.
- Good antiwear and Extreme Pressure properties.
- Excellent protection against corrosion and rust.
- Great resistance to foam formation.
- Excellent fluidity at low temperatures.
- Compatible with sealant materials.

Performance

- Reduces the formation of sludge, lacquer and varnish.
- High load-carrying capacity.
- Perfect lubrication at all operating speeds.
- Immediate oil circulation at start-up.
- Eliminates vibration and squealing in wet brakes.

Specifications

· API GL-4	· Allison C3/C4	· CAT TO-2	· VOLVO CE WB-101
· ZF TE-ML 03E/05F/06K/17E/21F	· MF CMS 1145/1143/1141/1135	· FNHA-2C-201.00 (ex FORD M2C-134D)	· CNH MAT 3525
· KUBOTA UDT	· John Deere JDM J20C/D		

Typical Characteristics

CHARACTERISTICS	ASTM STANDARD	AURIGA TE 55 10W30
SAE Grade	J300	10W-30
Density 15°C, g/cc	D-4052	0.8854
Flash Point (COC) °C	D-92	214
Pour Point, °C	D-97	-32
Viscosity at 40°C, cSt	D-445	56.46
Viscosity at 100°C, cSt	D-445	9.60
Viscosity Index	D-2270	155

Health & Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products..

The typical values of the characteristics appearing in the table are average values given for guidance purposes. These values may be modified without any prior warning.